



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M
FARBE	White/ True Blue
RAHMEN	ALUXX-Grade aluminum
GABEL	SR Suntour XCM RL 27.5, 100mm travel, remote lockout, with preload adjuster
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Connect Trail
VORBAU	Giant Sport, 6-degree
SATTELSTÜTZE	Giant Sport, 30.9x375mm
SATTEL	Liv Contact Comfort forward saddle with patented UniClip, DCF (Dynamic Cycling Fit), and ParticleFlow technology
PEDALE	MTB Caged, 9/16
ANTRIEB	
SCHALTHEBEL	Shimano Altus,SL-M2000
UMWERFER	Shimano Altus
SCHALTWERK	Shimano Alivio
BREMSEN	Tektro M275 [F] 160 [R] 160
BREMSHEBEL	Tektro
KASSETTE	Shimano HG201-9, 11x36
KETTE	KMC X9
KURBEL	ProWheel Virgor-401, 22/32/44
LAUFRÄDER	
TRETLAGER	Feimin FP-902W
FELGEN	Giant GX03V 27.5 6061 aluminum, double wall, 21mm inner width
NABE	Giant Tracker Sport, 32H, [F] QR [R] QR
SPEICHEN	stainless, 14G
REIFEN	Maxxis Ikon 60tpi wire 27.5X 2.2

MODELL-MERKMALE

- Rahmen: ALUXX-Grade aluminum
- Gabel: SR Suntour XCM RL 27.5, 100mm travel, remote lockout, with preload adjuster
- Schalthebel: Shimano Altus,SL-M2000
- Kurbel: ProWheel Virgor-401, 22/32/44
- Farbe: White/ True Blue

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	350	390	440	490
Sitzrohrwinkel	74.0°	73.5°	73.5°	73.0°
Oberrohrlänge (mm)	550	570	590	605
Steuerrohr-Länge (mm)	95	105	135	160
Steuerrohr-Winkel	68.0°	68.0°	68.0°	68.0°
Gabelneigung (mm)	42	42	42	42
Trail (mm)	99	99	99	99
Radstand (mm)	1082	1098	1121	1132
Kettenstreben-Länge (mm)	440	440	440	440
Tretlager-Höhe (mm)	45	45	45	45
Stack (mm)	572	582	609	633
Reach (mm)	386	397	409	411
Überstandshöhe (mm)	666	683	728	761
Lenkerbreite (mm)	690	690	750	750
Vorbaulänge (mm)	40	50	60	70
Kurbellänge (mm)	170	170	170	175
Radgrösse	27.5"	27.5"	27.5"	27.5"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.