



## SPEZIFIKATIONEN

| RAHMEN                    |  |
|---------------------------|--|
| GRÖSSEN                   | XS, S, M, L  |
| FARBE                     | Silver Pine  |
| RAHMEN                    | ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount |
| GABEL                     | RST Volante TNL coil, 60mm travel, tapered steerer, hydraulic lockout            |
| DÄMPFER                   | N/A  |
| KOMPONENTEN               |  |
| LENKER                    | Giant Connect XC Riser   |
| VORBAU                    | Giant Contact  |
| SATTELSTÜTZE              | Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium                          |
| SATTEL                    | Selle Royal Vivo WMN   |
| PEDALE                    | Aluminium Platform   |
| ANTRIEB                   |  |
| SCHALTHEBEL               | Shimano SL-M2000   |
| UMWERFER                  | Shimano FD-M371  |
| SCHALTWERK                | Shimano Deore  |
| BREMSEN                   | Shimano BR-MT200, hydraulic disc, 180mm  |
| BREMSHEBEL                | Shimano BL-MT200   |
| KASSETTE                  | Shimano CS-HG200, 11-36T, 9-Speed  |
| KETTE                     | KMC e9 Sport, e-bike optimized   |
| KURBEL                    | Forged Alloy minimal Q-factor, 36/48T  |
| LAUFRÄDER                 |  |
| TRETLAGER                 | N/A  |
| FELGEN                    | Giant eX2, Tubeless Ready, 700c aluminium, e-bike optimized                      |
| NABE                      | Giant eTracker, [F] 100x9mm QR [R] 135mm QR, e-bike optimized                    |
| SPEICHEN                  | Stainless steel  |
| REIFEN                    | Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready, Reflex                |
| EXTRAS                    | Giant EnergyPak 4A fast charger MIK system carrier top-deck                      |
| HYBRID CYCLING TECHNOLOGY |  |
| MOTOR                     | Giant SyncDrive Sport, 70Nm, 350% tuneable support with automatic smart support  |
| SENSORS                   | Giant PedalPlus 6-sensor technology  |
| DISPLAY                   | Giant RideControl Charge display   |
| BATTERY                   | Giant EnergyPak 500, 36V 13.8Ah Rechargeable Lithium-Ion                         |
| ACCESSORIES               |  |
| LIGHTING                  | Spanninga Axendo 40Lux front Axa BlueLine Steady E6 rear                         |
| LOCK                      | -  |

## MODELL-MERKMALE

- Rahmen: ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
- Gabel: RST Volante TNL coil, 60mm travel, tapered steerer, hydraulic lockout
- Schalthebel: Shimano SL-M2000
- Kurbel: Forged Alloy minimal Q-factor, 36/48T
- Farbe: Silver Pine

## GEOMETRIEDATEN

| RAHMEN                  | XS    | S     | M     | L     |
|-------------------------|-------|-------|-------|-------|
| Sitzrohrlänge (mm)      | 370   | 420   | 470   | 520   |
| Sitzrohrwinkel          | 74.0° | 73.5° | 73.5° | 73.0° |
| Oberrohrlänge (mm)      | 545   | 565   | 585   | 605   |
| Steuerrohr-Länge (mm)   | 135   | 135   | 155   | 175   |
| Steuerrohr-Winkel       | 69.5° | 69.5° | 69.5° | 69.5° |
| Gabelneigung (mm)       | 42    | 42    | 42    | 42    |
| Trail (mm)              | 91.3  | 91.3  | 91.3  | 91.3  |
| Radstand (mm)           | 1097  | 1111  | 1133  | 1148  |
| Kettenstaben-Länge (mm) | 470   | 470   | 470   | 470   |
| Tretlager-Höhe (mm)     | 60    | 60    | 60    | 60    |
| Stack (mm)              | 619   | 619   | 638   | 657   |
| Reach (mm)              | 367   | 382   | 396   | 406   |
| Überstandshöhe (mm)     | 616   | 596   | 584   | 570   |
| Lenkerbreite (mm)       | 620   | 620   | 640   | 640   |
| Vorbaulänge (mm)        | 70    | 80    | 80    | 90    |
| Kurbellänge (mm)        | 170   | 170   | 170   | 170   |
| Radgrösse               | 700c  | 700c  | 700c  | 700c  |

Spezifikations-, Preis- und Farbaenderungen vorbehalten.