



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Chameleon Saturn / Black
RAHMEN	Advanced-Grade Composite, 140mm
GABEL	RockShox 35, 150mm travel, DebonAir, Motion Control Damping, Boost, 15x110 Maxle Stealth, tapered
DÄMPFER	RockShox Deluxe Select
KOMPONENTEN	
LENKER	Giant Contact SL TR35, 780x35
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Giant Contact Switch dropper, remote lever, 30.9
SATTEL	Liv Contact SL (forward)
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM SX Eagle
UMWERFER	N/A
SCHALTWERK	SRAM SX
BREMSEN	Shimano BR-MT420, hydraulic disc
BREMSHEBEL	Shimano MT-401
KASSETTE	SRAM SX Eagle, 11x50
KETTE	SRAM SX Eagle
KURBEL	SRAM SX Eagle DUB, 30t
LAUFRÄDER	
TRETLAGER	SRAM DUB, press fit
FELGEN	Giant TRX-1 Composite WheelSystem
NABE	Giant TRX-1 WheelSystem
SPEICHEN	Giant TRX-1 WheelSystem
REIFEN	[F] Maxxis High Roller II 27.5x2.5 WT, 3C, EXO, TR [R] Maxxis High Roller II 27.5x2.4, 3C, EXO, TR, tubeless
EXTRAS	Tubeless prepared

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite, 140mm
- Gabel: RockShox 35, 150mm travel, DebonAir, Motion Control Damping, Boost, 15x110 Maxle Stealth, tapered
- Schalthebel: SRAM SX Eagle
- Kurbel: SRAM SX Eagle DUB, 30t
- Farbe: Chameleon Saturn / Black

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	380	406	445	482
Sitzrohrwinkel	74.5°	74.5°	74.5°	74.5°
Oberrohrlänge (mm)	565	580	595	620
Steuerrohr-Länge (mm)	95	100	105	125
Steuerrohr-Winkel	66.5°	66.5°	66.5°	66.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	109.6	109.6	109.6	109.6
Radstand (mm)	1135	1151	1167	1195
Kettenstreben-Länge (mm)	438	438	438	438
Tretlager-Höhe (mm)	15	15	15	15
Stack (mm)	577	582	587	605
Reach (mm)	405	418	432	452
Überstandshöhe (mm)	691	707	735	751
Lenkerbreite (mm)	760	760	780	780
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	165	170	170	170
Radgrösse	27.5"	27.5"	27.5"	27.5"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.