



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Light Blue / Ocean Depths
RAHMEN	ALUXX SL-Grade Aluminum, 140mm
GABEL	Fox 34 Rhythm, 150mm , GRIP damper, Boost, 15x110, tapered
DÄMPFER	Fox Float DPS Performance
KOMPONENTEN	
LENKER	Giant Connect Trail, 780x31.8
VORBAU	Giant Contact
SATTELSTÜTZE	Giant Contact Switch dropper, remote lever, 30.9
SATTEL	Liv Contact (forward)
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM NX Eagle
UMWERFER	N/A
SCHALTWERK	SRAM NX Eagle
BREMSEN	Shimano BR-MT520, hydraulic disc
BREMSHEBEL	Shimano BL-MT501
KASSETTE	SRAM NX Eagle, 11x50
KETTE	SRAM NX Eagle
KURBEL	TruVativ Descendent 6k Eagle DUB, 30t
LAUFRÄDER	
TRETLAGER	SRAM DUB, press fit
FELGEN	Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width
NABE	[F] Giant Tracker Boost 15x110, sealed bearing [R] Giant Tracker Boost 12x148, sealed bearing
SPEICHEN	Sapim
REIFEN	[F] Maxxis High Roller II 27.5x2.5 WT, EXO, TR [R] Maxxis High Roller II 27.5x2.4, EXO, TR, tubeless
EXTRAS	Tubeless prepared

MODELL-MERKMALE

- Rahmen: ALUXX SL-Grade Aluminum, 140mm
- Gabel: Fox 34 Rhythm, 150mm , GRIP damper, Boost, 15x110, tapered
- Schalthebel: SRAM NX Eagle
- Kurbel: TruVativ Descendent 6k Eagle DUB, 30t
- Farbe: Light Blue / Ocean Depths

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	380	406	445	482
Sitzrohrwinkel	74.5°	74.5°	74.5°	74.5°
Oberrohrlänge (mm)	565	580	595	620
Steuerrohr-Länge (mm)	95	100	105	125
Steuerrohr-Winkel	66.5°	66.5°	66.5°	66.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	110	110	110	110
Radstand (mm)	1135	1151	1167	1195
Kettenstreben-Länge (mm)	438	438	438	438
Tretlager-Höhe (mm)	15	15	15	15
Stack (mm)	577	582	587	605
Reach (mm)	405	418	432	452
Überstandshöhe (mm)	692	711	738	762
Lenkerbreite (mm)	760	760	780	780
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	165	170	170	170
Radgrösse	27.5"	27.5"	27.5"	27.5"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.