

VALL E+ 3 POWER



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Starry Gray / Metallic Purple
RAHMEN	ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, 141mm Boost QR, integrated KS18 kickstand mount
GABEL	SR Suntour XCM34 Boost Coil NLO 27,5+ 120mm travel, Tapered 1½ - 1⅝" steerer, lockout
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Connect TR Riser
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Liv Sport
PEDALE	Aluminum Platform
ANTRIEB	
SCHALTHEBEL	Shimano SL-M2000
UMWERFER	-
SCHALTWERK	Shimano Deore, 9-Speed, Shadow design
BREMSSEN	Tektro HD-M286, hydraulic disc, 180mm
BREMSHEBEL	Tektro HD-M285
KASSETTE	Shimano CS-HG200, 11-36T, 9-Speed
KETTE	KMC e.9 Sport, e-bike optimized
KURBEL	Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring
LAUFRÄDER	
TRETLAGER	N/A
FELGEN	Giant AM 27.5, Tubeless ready, 30mm inner width, e-bike optimized
NABE	Giant eTracker Boost, [F] 15mm Thru-Axle [R] 148x12mm Thru-axle, e-bike optimized
SPEICHEN	Stainless steel
REIFEN	Maxxis Forekaster 27.5x2.6, foldable, 60 TPI, EXO, Tubeless ready
EXTRAS	Giant EnergyPak 4A fast charger
HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport, 70Nm, 350% tuneable support with automatic smart support
SENSORS	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl ONE, remote button
BATTERY	Giant EnergyPak500, 36V 13.8Ah Rechargeable Lithium-Ion

MODELL-MERKMALE

- Rahmen: ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, 141mm Boost QR, integrated KS18 kickstand mount
- Gabel: SR Suntour XCM34 Boost Coil NLO 27,5+ 120mm travel, Tapered 1½ - 1⅝" steerer, lockout
- Schalthebel: Shimano SL-M2000
- Kurbel: Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring
- Farbe: Starry Gray / Metallic Purple

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohlänge (mm)	365	405	460	510
Sitzrohrwinkel	74.0°	73.5°	73.0°	73.0°
Oberrohrlänge (mm)	550	565	585	600
Steuerrohr-Länge (mm)	110	115	135	150
Steuerrohr-Winkel	68.0°	68.0°	68.0°	68.0°
Gabelneigung (mm)	42	42	42	42
Trail (mm)	100.2	100.2	100.2	100.2
Radstand (mm)	1116	1126	1142	1158
Kettenstreben-Länge (mm)	475	475	475	475
Tretlager-Höhe (mm)	50	50	50	50
Stack (mm)	612	617	635	649
Reach (mm)	374	382	390	401
Überstandshöhe (mm)	674	696	742	763
Lenkerbreite (mm)	690	690	750	750
Vorbaulänge (mm)	50	50	60	70
Kurbellänge (mm)	170	170	170	170
Radgrösse	27.5+	27.5+	27.5+	27.5+

Spezifikations-, Preis- und Farbaenderungen vorbehalten.