



## SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport
DISPLAY	Giant RideControl Plus (optional)
BATTERY	Giant EnergyPak Smart 625, 36V Integrated Lithium-Ion
RAHMEN	
GRÖSSEN	XS, S, M, L (XS-S: 27.5", M-L: 29")
FARBE	Rosewood
RAHMEN	ALUXX SL-Grade Aluminum, 120mm FlexPoint Suspension System
GABEL	RockShox Recon Silver RL, 130mm travel, Lockout, 110x15mm Boost, Maxle Stealth, e-MTB optimized
DÄMPFER	RockShox Monarch RT, High Volume, 184x44mm, custom tuned
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x750~780mm (XS-S: 750 / M-L: 780)
VORBAU	Giant Contact
SATTELSTÜTZE	Giant Contact Switch, dropper, 30,9mm
SATTEL	Liv Contact Upright
PEDALE	Flatpedal
ANTRIEB	
SCHALTHEBEL	SRAM SX Eagle 12-speed
UMWERFER	-
SCHALTWERK	SRAM SX Eagle 12-speed
BREMSEN	Shimano MT420, 4-piston, hydraulic disc, 203mm
BREMSHEBEL	Shimano MT401
KASSETTE	SRAM PG-1210, 11-50T, 12-Speed
KETTE	KMC e.12 Turbo, EcoProtec, e-bike optimized
KURBEL	SRAM X-Sync Eagle 38T 104BCD chainring Forged Alloy minimal Q-factor, 38T Steel Direct Mount ring (XS/S:160, M/L:165)
TRETLAGER	N/A
LAUFRÄDER	
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR
SPEICHEN	Stainless Steel
REIFEN	Maxxis Rekon 29x2.4/27.5x2.4 Foldable, 60TPI, EXO, Tubeless Ready (XS-S: 27.5", M-L: 29")
EXTRAS	Giant EnergyPak 6A Smart charger

## MODELL-MERKMALE

- Rahmen: ALUXX SL-Grade Aluminum, 120mm FlexPoint Suspension System
- Gabel: RockShox Recon Silver RL, 130mm travel, Lockout, 110x15mm Boost, Maxle Stealth, e-MTB optimized
- Schalthebel: SRAM SX Eagle 12-speed
- Kurbel: SRAM X-Sync Eagle 38T 104BCD chainring Forged Alloy minimal Q-factor, 38T Steel Direct Mount ring (XS/S:160, M/L:165)
- Farbe: Rosewood

## GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	380	406	445	490
Sitzrohrwinkel	74.0°	74.0°	74.0°	74.0°
Oberrohrlänge (mm)	565	580	595	610
Steuerrohr-Länge (mm)	100	100	110	120
Steuerrohr-Winkel	67.5°	67.5°	67.5°	67.5°
Gabelneigung (mm)	46	46	46	46
Trail (mm)	103.5	103.5	103.5	103.5
Radstand (mm)	1157	1172	1188	1204
Kettenstreben-Länge (mm)	475	475	475	475
Tretlager-Höhe (mm)	20	20	20	20
Stack (mm)	594	594	603	612
Reach (mm)	395	410	422	434
Überstandshöhe (mm)	710	738	765	786
Lenkerbreite (mm)	750	750	780	780
Vorbaulänge (mm)	40	40	50	60
Kurbellänge (mm)	160	165	165	170
Radgrösse	27.5+	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.