

INTRIGUE ADVANCED PRO 29 0



Spezifikationen

Rahmen	
Größen	S, M, L
Farbe	Supernova
Rahmen	Advanced-Grade Composite front and rear triangles, 125mm Maestro Suspension, flip chip
Gabel	Fox 36 Factory Live Valve, 140mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv
Dämpfer	Fox Float DPX2 Factory Live Valve [185/50], custom tuned for Liv
Komponenten	
Lenker	Giant Contact SLR TR35, 780x35
Vorbau	Giant Contact SL 35
Sattelstütze	Fox Transfer Factory dropper, Shimano remote lever, 30.9
Sattel	Liv Sylvia SL
Pedale	N/A
Antrieb	
Schalthebel	Shimano Deore XT
Umwerfer	N/A
Schaltwerk	Shimano XTR
Bremsen	Shimano Deore XT
Bremshebel	Shimano Deore XT
Kassette	Shimano Deore XT, 10x51
Kette	Shimano
Kurbel	Shimano Deore XT, 30t with MRP AMg V2 carbon guide
Tretlager	Shimano, press fit
Laufräder	
Felgen	Giant TRX-1 29 WheelSystem
Nabe	Giant TRX-1 29 WheelSystem
Speichen	Giant TRX-1 29 WheelSystem
Reifen	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
Extras	tubeless prepared

Modell-Merkmale

- Rahmen: Advanced-Grade Composite front and rear triangles, 125mm Maestro Suspension, flip chip
- Gabel: Fox 36 Factory Live Valve, 140mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv
- Schalthebel: Shimano Deore XT
- Kurbel: Shimano Deore XT, 30t with MRP AMg V2 carbon guide
- Farbe: Supernova

Geometriedaten

Rahmen	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohlänge (mm)	425	435	460
Sitzrohrwinkel	77.0° 77.8°	77.0° 77.8°	77.0° 77.8°
Oberrohrlänge (mm)	558 557	574 573	599 597
Steuerrohr-Länge (mm)	105	110	125
Steuerrohr-Winkel	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°
Gabelneigung (mm)	44	44	44
Trail (mm)	122 117	122 117	122 117
Radstand (mm)	1160 1160	1177 1176	1205 1204
Kettenstreben-Länge (mm)	438 435	438 435	438 435
Tretlager-Höhe (mm)	40 30	40 30	40 30
Stack (mm)	620 614	625 618	639 632
Reach (mm)	415 424	430 438	451 460
Überstandshöhe (mm)	742 751	732 741	751 759
Lenkerbreite (mm)	760	760	780
Vorbaulänge (mm)	50	50	50
Kurbellänge (mm)	170	170	175
Radgrösse	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.