

LANGMA ADVANCED PRO 0 DISC



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XXS, XS, S, M, L
FARBE	Dark Iridescent
RAHMEN	Advanced-Grade Composite, disc
GABEL	Advanced-Grade Composite, full-composite OverDrive 2 steerer, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact SL
VORBAU	Giant Contact SL
SATTELSTÜTZE	Giant Variant, composite
SATTEL	Liv Alacra SLR
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano Ultegra Di2
UMWERFER	Shimano Ultegra Di2
SCHALTWERK	Shimano Ultegra Di2
BREMSEN	Shimano Ultegra hydraulic disc
BREMSHEBEL	Shimano Ultegra hydraulic
KASSETTE	Shimano Ultegra, 11x30
KETTE	KMC X11SL-1
KURBEL	Shimano Ultegra, 36/52, Giant Power Pro power meter
TRETLAGER	Shimano, press fit
LAUFRÄDER	
FELGEN	Giant SLR 1 42 Disc WheelSystem
NABE	Giant SLR 1 42 Disc WheelSystem
SPEICHEN	Giant SLR 1 42 Disc WheelSystem
REIFEN	CADEX Road Race, 700x25c, tubeless
EXTRAS	tubeless prepared

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite, disc
- Gabel: Advanced-Grade Composite, full-composite OverDrive 2 steerer, disc
- Schalthebel: Shimano Ultegra Di2
- Kurbel: Shimano Ultegra, 36/52, Giant Power Pro power meter
- Farbe: Dark Iridescent

GEOMETRIEDATEN

RAHMEN	XXS	XS	S	M	L
Sitzrohrlänge (mm)	385	410	445	480	515
Sitzrohrwinkel	75.0°	75.0°	74.5°	74.0°	73.5°
Oberrohrlänge (mm)	497	507	524	540	555
Steuerrohr-Länge (mm)	100	115	130	150	170
Steuerrohr-Winkel	70.5°	71.0°	72.0°	72.5°	72.5°
Gabelneigung (mm)	49	49	45	45	45
Trail (mm)	68.8	65.6	63.5	60.3	60.3
Radstand (mm)	966	972	974	981	991
Kettenstreben-Länge (mm)	405	405	405	405	405
Tretlager-Höhe (mm)	70	70	68	68	68
Stack (mm)	492	508	525	546	565
Reach (mm)	365	371	378	384	388
Überstandshöhe (mm)	664	679	701	728	754
Lenkerbreite (mm)	360	360	380	400	420
Vorbaulänge (mm)	80	80	90	100	110
Kurbellänge (mm)	165	165	170	170	172.5
Radgrösse	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbaenderungen vorbehalten.