



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	27.5": XS,S,M 29": S,M,L
FARBE	Rosewood
RAHMEN	ALUXX-Grade Aluminum
GABEL	SXC32-2 RRL 29 or 27.5, air spring, 100mm or 80mm, QR, alloy steerer, rebound adjustable, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Connect Trail, 780x31.8
VORBAU	Giant Sport, 7-degree
SATTELSTÜTZE	Giant Sport, 30.9
SATTEL	Liv Sport
PEDALE	MTB caged
ANTRIEB	
SCHALTHEBEL	Shimano Deore M5100
UMWERFER	Shimano Deore M5100
SCHALTWERK	Shimano Deore M4100
BREMSEN	Shimano BR-MT200, hydraulic
BREMSHEBEL	Shimano BL-MT200
KASSETTE	Shimano Deore M5100, 11x42
KETTE	KMC X11
KURBEL	Praxis Cadet, 22/36
TRETLAGER	cartridge
LAUFRÄDER	
FELGEN	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NABE	[F]Giant Tracker Giant Sport QR, loose ball [R] Giant Tracker Giant Sport QR, loose ball
SPEICHEN	stainless, 14g
REIFEN	Maxxis Rekon 27.5 or 29x2.4, wire bead

MODELL-MERKMALE

- Rahmen: ALUXX-Grade Aluminum
- Gabel: SXC32-2 RRL 29 or 27.5, air spring, 100mm or 80mm, QR, alloy steerer, rebound adjustable, disc
- Schalthebel: Shimano Deore M5100
- Kurbel: Praxis Cadet, 22/36
- Farbe: Rosewood

GEOMETRIEDATEN

RAHMEN	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")
Sitzrohrlänge (mm)	325	365	370	405	420	450
Sitzrohrwinkel	74.0°	74.0°	74.0°	74.0°	74.0°	74.0°
Oberrohrlänge (mm)	542	571	570	594	590	610
Steuerrohr-Länge (mm)	95	100	90	110	95	105
Steuerrohr-Winkel	68.0°	68.0°	68.5°	68.0°	68.5°	68.5°
Gabelneigung (mm)	40	42	51	42	51	51
Trail (mm)	102	98.9	94.3	98.9	94.3	94.3
Radstand (mm)	1072	1104	1119	1128	1139	1160
Kettenstreben-Länge (mm)	440	440	455	440	455	455
Tretlager-Höhe (mm)	40	45	55	45	55	55
Stack (mm)	554	579	596	588	601	610
Reach (mm)	383	405	399	425	418	435
Überstandshöhe (mm)	663	686	705	708	737	757
Lenkerbreite (mm)	730	750	750	750	750	750
Vorbaulänge (mm)	40	40	40	50	50	50
Kurbellänge (mm)	165	165	170	170	170	175
Radgrösse	27.5"	27.5"	29"	27.5"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.