



## SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport
DISPLAY	Giant RideControl Plus
BATTERY	Giant EnergyPak Smart 500, 36V Integrated Lithium-Ion
RAHMEN	
GRÖSSEN	XS, S, M, L (XS-S: 27.5", M-L: 29")
FARBE	Echeveria
RAHMEN	ALUXX SL-Grade Aluminum, Overdrive 1½ - 1⅝ inch headtube, 141mm Boost QR, integrated KS18 kickstand mount
GABEL	SR Suntour XCR 32 Boost Coil LOR 27.5 / 29 120mm travel, Tapered 1½ - 1⅝ inch steerer, lockout (XS-S: 27.5", M-L: 29")
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x690-750mm (XS-S: 690 / M-L: 750)
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Liv Sport
PEDALE	Aluminium Plattform
ANTRIEB	
SCHALTHEBEL	Shimano Deore
UMWERFER	chainguide
SCHALTWERK	Shimano Deore, 10-Speed, Shadow+
BREMSEN	Shimano BR-MT200, hydraulic disc, 180mm
BREMSHEBEL	Shimano BL-MT200
KASSETTE	Shimano CS-M4100-10 11-46T 10-Speed
KETTE	KMC e.10 Sport, E-bike optimized
KURBEL	Forged Alloy minimal Q-factor, 36T Steel Direct Mount
LAUFRÄDER	
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized Giant AM 27.5, Tubeless ready, 30mm inner width, e-bike optimized (XS-S: 27.5, M-L: 29er)
NABE	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR, e-bike optimized
SPEICHEN	Stainless steel
REIFEN	Maxxis Rekon 29x2.4 / 27.5x2.4, Foldable, EXO, Tubeless Ready (XS-S: 27.5", M-L: 29")
EXTRAS	Giant EnergyPak 6A Smart charger Giant EnergyPak Plus range extender compatible

## MODELL-MERKMALE

- Rahmen: ALUXX SL-Grade Aluminum, Overdrive 1½ - 1⅝ inch headtube, 141mm Boost QR, integrated KS18 kickstand mount
- Gabel: SR Suntour XCR 32 Boost Coil LOR 27.5 / 29 120mm travel, Tapered 1½ - 1⅝ inch steerer, lockout (XS-S: 27.5", M-L: 29")
- Schalthebel: Shimano Deore
- Kurbel: Forged Alloy minimal Q-factor, 36T Steel Direct Mount
- Farbe: Echeveria

## GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	365	405	445	485
Sitzrohrwinkel	74.0°	73.5°	73.0°	73.0°
Oberrohrlänge (mm)	560	565	595	615
Steuerrohr-Länge (mm)	110	115	105	115
Steuerrohr-Winkel	68.0°	68.0°	68.0°	68.0°
Gabelneigung (mm)	42	42	46	46
Trail (mm)	103.8	103.8	99.5	99.5
Radstand (mm)	1130	1130	1161	1182
Kettenstreben-Länge (mm)	475	475	475	475
Tretlager-Höhe (mm)	50	50	45	45
Stack (mm)	621	626	625	634
Reach (mm)	382	380	404	421
Überstandshöhe (mm)	680	710	750	755
Lenkerbreite (mm)	690	690	750	750
Vorbaulänge (mm)	40	50	50	60
Kurbellänge (mm)	165	165	170	170
Radgröße	27.5+	27.5+	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.