



## SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro
DISPLAY	Giant RideControl EVO
BATTERY	Giant EnergyPak Smart 625, 36V Integrated Lithium-Ion
RAHMEN	
GRÖSSEN	XS, S, M, L (XS-S: 27.5", M-L: 29")
FARBE	Dark Iridescent
RAHMEN	ALUXX SL-Grade Aluminum, Overdrive 1½ - 1⅛ inch headtube, 148x12mm Thru-Axle, integrated KS18 kickstand mount
GABEL	SR Suntour Raidon 34 Boost Air LOR 27.5 / 29 120mm travel, Tapered 1½ - 1⅛" steerer, lockout (XS-S: 27.5", M-L: 29")
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x690-750mm (XS-S: 690 / M-L: 750)
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Liv Sport
PEDALE	Aluminium Platform
ANTRIEB	
SCHALTHEBEL	Shimano Deore
UMWERFER	chainguide
SCHALTWERK	Shimano Deore, 11-Speed, Shadow+
BREMSEN	Shimano BR-MT200, hydraulic disc, 180mm
BREMSHEBEL	Shimano BL-MT200
KASSETTE	Shimano CS-M5100 11-51T 11-Speed
KETTE	KMC e11 Sport EPT E-bike optimized
KURBEL	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
LAUFRÄDER	
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Giant eTracker Boost, Sealed cartridge bearing, 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle
SPEICHEN	Stainless steel
REIFEN	Maxxis DHF 29x2.5 / 27.5x 2.5 WT Foldable 60TPI TLR EXO [F] Maxxis Aggressor 29x2.5 / 27.5x 2.5 WT Foldable 60TPI TLR EXO [R] (XS-S: 27.5", M-L: 29")
EXTRAS	Giant EnergyPak 6A Smart charger Giant EnergyPak Plus range extender compatible

## MODELL-MERKMALE

- Rahmen: ALUXX SL-Grade Aluminum, Overdrive 1½ - 1⅛ inch headtube, 148x12mm Thru-Axle, integrated KS18 kickstand mount
- Gabel: SR Suntour Raidon 34 Boost Air LOR 27.5 / 29 120mm travel, Tapered 1½ - 1⅛" steerer, lockout (XS-S: 27.5", M-L: 29")
- Schalthebel: Shimano Deore
- Kurbel: Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
- Farbe: Dark Iridescent

## GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	365	405	445	485
Sitzrohrwinkel	74.0°	73.5°	73.0°	73.0°
Oberrohrlänge (mm)	560	565	595	615
Steuerrohr-Länge (mm)	110	115	105	115
Steuerrohr-Winkel	68.0°	68.0°	68.0°	68.0°
Gabelneigung (mm)	42	42	46	46
Trail (mm)	103.8	103.8	99.5	99.5
Radstand (mm)	1130	1130	1161	1182
Kettenstreben-Länge (mm)	475	475	475	475
Tretlager-Höhe (mm)	50	50	45	45
Stack (mm)	621	626	625	634
Reach (mm)	382	380	404	421
Überstandshöhe (mm)	681	704	749	777
Lenkerbreite (mm)	690	690	750	750
Vorbaulänge (mm)	40	50	50	60
Kurbellänge (mm)	165	165	170	170
Radgrösse	27.5+	27.5+	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.