



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XXS, XS, S, M, L
FARBE	Twilight Mauve, Fanatic Teal
RAHMEN	Advanced-Grade Composite, 12x142mm thru-axle, disc
GABEL	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Liv Contact SL D-Fuse, 31.8mm XXS:38cm, XS:38cm, S:40cm, M:40cm, L:42cm
GRIPS	Liv All Condition
VORBAU	Giant Contact XXS:70mm, XS:70mm, S:80mm, M:90mm, L:90mm
SATTELSTÜTZE	Giant D-Fuse, composite, -5/+15mm offset XXS:350mm, XS:350mm, S:350mm, M:350mm, L:350mm
SATTEL	Liv Approach
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano 105 ST-7025
UMWERFER	Shimano 105
SCHALTWERK	Shimano 105
BREMSEN	Shimano 105 hydraulic, Shimano rotors [F]160mm, [R]140mm
BREMSHEBEL	Shimano Ultegra
KASSETTE	Shimano 105, 11-speed, 11x34
KETTE	KMC X11EL-1
KURBEL	Shimano RS510, 34/50 XXS:165mm, XS:165mm, S:170mm, M:170mm, L:172.5mm
TRETLAGER	Shimano, press fit
LAUFRÄDER	
FELGEN	Giant P-R2 Disc wheelset
NABE	Giant P-R2 Disc wheelset, 12mm thru-axle
SPEICHEN	Giant P-R2 Disc wheelset
REIFEN	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRAS	tubeless prepared, 35mm max tire size

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite, 12x142mm thru-axle, disc
- Gabel: Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm, disc
- Schalthebel: Shimano 105 ST-7025
- Kurbel: Shimano RS510, 34/50 XXS:165mm, XS:165mm, S:170mm, M:170mm, L:172.5mm
- Farbe: Twilight Mauve, Fanatic Teal

GEOMETRIEDATEN

RAHMEN	XXS	XS	S	M	L
Sitzrohrlänge (mm)	385	400	435	470	505
Sitzrohrwinkel	75.0°	74.5°	74.5°	74.0°	74.0°
Oberrohrlänge (mm)	500	515	525	540	555
Steuerrohr-Länge (mm)	110	125	145	165	185
Steuerrohr-Winkel	70.0°	70.5°	71.5°	72.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50
Trail (mm)	74.5	71.3	64.7	61.5	61.5
Radstand (mm)	988	995	998	1004	1020
Kettenstreben-Länge (mm)	420	420	420	420	420
Tretlager-Höhe (mm)	75	75	73	73	73
Stack (mm)	511	527	547	568	587
Reach (mm)	363	368	373	377	387
Überstandshöhe (mm)	661	684	716	745	772
Lenkerbreite (mm)	380	380	400	400	420
Vorbaulänge (mm)	70	70	80	90	90
Kurbellänge (mm)	165	165	170	170	172.5
Radgrösse	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.