EMBOLDEN 1

SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	27.5": XS, S, M 29": S, M, L
FARBE	Matte Black / Gloss Sparkling Black
RAHMEN	ALUXX-Grade Aluminum, 120mm FlexPoint Suspension
GABEL	Giant Crest 34 SL RCL, 130mm, 15x110
DÄMPFER	RockShox Monarch R, 184.15/44.45, custom tuned for Liv
KOMPONENTEN	
LENKER	Giant Connect Trail, Alloy For 27.5: XS:730mm, S:750mm, M:750mm For 29: S:750mm, M:750mm, L:780mm
GRIPS	Giant Sole-O
VORBAU	Giant Contact For 27.5: XS:40mm, S:50mm, M:50mm For 29: S:50mm, M:50mm, L:60mm
SATTELSTÜTZE	Giant Contact Switch dropper, remote For 27.5: XS: 75mm travel / 30.9 x 295mm S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm For 29: S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 125mm travel / 30.9 x 395mm
SATTEL	Liv Sylvia
PEDALE	platform
ANTRIEB	
SCHALTHEBEL	SRAM SX Eagle, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM SX Eagle
BREMSEN	Shimano BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
BREMSHEBEL	Shimano BL-MT401
KASSETTE	SRAM SX Eagle, 11x50
KETTE	SRAM SX Eagle
KURBEL	SRAM SX Eagle DUB, 30t For 27.5: XS:165mm, S:170mm, M:170mm For 29: S:170mm, M:170mm, L:170mm
TRETLAGER	SRAM DUB, press fit
LAUFRÄDER	
FELGEN	"For 27.5: Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width For 29: Giant AM 29, tubeless ready, sleeve-joint rim, 30mm inner width"
NABE	alloy, loose ball
SPEICHEN	Sapim
REIFEN	For 27.5: [F] Maxxis Rekon 27.5x2.6 WT, EXO, TR, tubeless [R] Maxxis Ardent Race 27.5x2.6 WT, EXO, TR, tubeless For 29: [F/R] Maxxis Forecaster 29x2.35 WT, EXO, TR, tubeless
EXTRAS	For 27.5: tubeless prepared, max tire size 2.6", max chainring size 32t

MODELL-MERKMALE

- Rahmen: ALUXX-Grade Aluminum, 120mm FlexPoint Suspension
- Gabel: Giant Crest 34 SL RCL, 130mm, 15x110
- Schalthebel: SRAM SX Eagle, 1x12
- Kurbel: SRAM SX Eagle DUB, 30t For 27.5: XS:165mm, S:170mm, M:170mm For 29: S:170mm, M:170mm, L:170mm
- Farbe: Matte Black / Gloss Sparkling Black

GEOMETRIEDATEN

RAHMEN	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")
Sitzrohrlänge (mm)	380	406	405	445	420	440
Sitzrohrwinkel	74.0°	74.0°	76.0°	74.0°	76.0°	76.0°
Oberrohrlänge (mm)	565	580	565	595	585	605
Steuerrohr-Länge (mm)	95	100	105	110	115	125
Steuerrohr-Winkel	67.5°	67.5°	67.0°	67.5°	67.0°	67.0°
Gabelneigung (mm)	43	43	51	43	51	51
Trail (mm)	103.6	103.6	105.3	103.6	105.3	105.3
Radstand (mm)	1109	1125	1147	1141	1169	1190
Kettenstreben-Länge (mm)	435	435	438	435	438	438
Tretlager-Höhe (mm)	20	20	40	20	40	40
Stack (mm)	560	565	614	574	623	632
Reach (mm)	404	418	412	430	430	447
Überstandshöhe (mm)	690	705	712	733	734	755
Lenkerbreite (mm)	750	750	740	780	760	780
Vorbaulänge (mm)	40	40	40	50	50	50
Kurbellänge (mm)	165	170	170	170	170	170
Radgrösse	27.5"	27.5"	29"	27.5"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.