

INTRIGUE ADVANCED PRO 29 2



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L
FARBE	Fanatic Teal / Carbon / Chrome
RAHMEN	Advanced-Grade Composite front and rear triangles, 125mm Maestro Suspension, flip chip
GABEL	Fox 34 Float Rhythm, 140mm, GRIP damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv
DÄMPFER	Fox Float DPS Performance 185/50, custom tuned for Liv
KOMPONENTEN	
LENKER	Giant Contact TR35, alloy, 35mm S:760mm, M:760mm, L:780mm
GRIPS	Liv Supera, single lock ring
VORBAU	Giant Contact SL, 35mm S:50mm, M:50mm, L:50mm
SATTELSTÜTZE	TranzX travel-adjustable dropper, remote S: 95-125mm travel / 30.9 x 409mm M: 120-150mm travel / 30.9 x 459mm L: 140-170mm travel / 30.9 x 499mm
SATTEL	Liv Sylvia SL
PEDALE	platform
ANTRIEB	
SCHALTHEBEL	Shimano SLX M7100, 1x12
UMWERFER	N/A
SCHALTWERK	Shimano SLX M7100
BREMSEN	Shimano M6120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BREMSHEBEL	Shimano Deore BL-M6100
KASSETTE	Shimano SLX M7100, 10x51
KETTE	KMC X-12
KURBEL	Shimano MT511, 30t S:170mm, M:170mm, L:170mm
TRETLAGER	Shimano, press fit
LAUFRÄDER	
FELGEN	Giant TRX-2 Carbon 29 WheelSystem
NABE	Giant TRX-2 Carbon 29 WheelSystem
SPEICHEN	Giant TRX-2 Carbon 29 WheelSystem
REIFEN	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.5", max chainring size 32t

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite front and rear triangles, 125mm Maestro Suspension, flip chip
- Gabel: Fox 34 Float Rhythm, 140mm, GRIP damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv
- Schalthebel: Shimano SLX M7100, 1x12
- Kurbel: Shimano MT511, 30t S:170mm, M:170mm, L:170mm
- Farbe: Fanatic Teal / Carbon / Chrome

GEOMETRIEDATEN

RAHMEN	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohrlänge (mm)	425	435	460
Sitzrohrwinkel	77.0° 77.8°	77.0° 77.8°	77.0° 77.8°
Oberrohrlänge (mm)	558 557	574 573	599 597
Steuerrohr-Länge (mm)	105	110	125
Steuerrohr-Winkel	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°
Gabelneigung (mm)	44	44	44
Trail (mm)	122 117	122 117	122 117
Radstand (mm)	1160 1160	1177 1176	1205 1204
Kettenstreben-Länge (mm)	438 435	438 435	438 435
Tretlager-Höhe (mm)	40 30	40 30	40 30
Stack (mm)	620 614	625 618	639 632
Reach (mm)	415 424	430 438	451 460
Überstandshöhe (mm)	731 740	737 746	756 765
Lenkerbreite (mm)	760	760	780
Vorbaulänge (mm)	50	50	50
Kurbellänge (mm)	170	170	175
Radgrösse	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.