



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XXS, XS, S, M, L
FARBE	Artic Light, Chrome
RAHMEN	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
GABEL	Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, 12x100mm, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Liv Contact SLR XXS:36cm, XS:36cm, S:38cm, M:40cm, L:42cm
GRIPS	Liv All Condition
VORBAU	Giant Contact SLR XXS:80mm, XS:80mm, S:90mm, M:100mm, L:110mm
SATTELSTÜTZE	Giant Variant SLR, composite XXS:357mm, XS:357mm, S:357mm, M:357mm, L:357mm
SATTEL	Liv Alacra SLR CS
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano Dura-Ace Di2 ST-R9270
UMWERFER	Shimano Dura-Ace Di2 ST-R9250
SCHALTWERK	Shimano Dura-Ace Di2 ST-R9250
BREMSEN	Shimano Dura-Ace Di2 hydraulic, Shimano RT-MT900 rotors [F]160mm, [R]140mm
BREMSHEBEL	Shimano Dura-Ace Di2
KASSETTE	Shimano Dura-Ace, 12-speed, 11x34
KETTE	Shimano Dura-Ace M9100
KURBEL	Shimano Dura-Ace, 36/52with FC-9200P power meterXXS:170mm, XS:170mm, S:170mm, M:170mm, L:172.5mm
TRETLAGER	Shimano, press fit
LAUFRÄDER	
FELGEN	CADEX 36 Carbon Disc WheelSystem
NABE	CADEX 36 Carbon Disc WheelSystem, 12mm thru-axle
SPEICHEN	CADEX 36 Carbon Disc WheelSystem
REIFEN	CADEX Road Race, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, tubeless prepared, 32mm max tire size

MODELL-MERKMALE

- Rahmen: Advanced SL-Grade Composite, 12x142mm thru-axle, disc
- Gabel: Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, 12x100mm, disc
- Schalthebel: Shimano Dura-Ace Di2 ST-R9270
- Kurbel: Shimano Dura-Ace, 36/52with FC-9200P power meterXXS:170mm, XS:170mm, S:170mm, M:170mm, L:172.5mm
- Farbe: Artic Light, Chrome

GEOMETRIEDATEN

RAHMEN	XXS	XS	S	M	L
Sitzrohrlänge (mm)	390	420	450	480	510
Sitzrohrwinkel	75.0°	75.0°	74.5°	74.0°	73.5°
Oberrohrlänge (mm)	498	508	524	540	555
Steuerrohr-Länge (mm)	105	120	135	155	175
Steuerrohr-Winkel	70.0°	71.0°	72.0°	72.5°	72.5°
Gabelneigung (mm)	49	49	49	49	49
Trail (mm)	74.3	67.8	61.4	58.2	58.2
Radstand (mm)	970.4	973	977.2	984.2	995.5
Kettenstreben-Länge (mm)	405	405	405	405	405
Tretlager-Höhe (mm)	72	72	69.5	69.5	67
Stack (mm)	498.8	516.5	531.8	552.6	569.2
Reach (mm)	364.4	369.6	376.5	381.5	386.4
Überstandshöhe (mm)	680	700	730	760	790
Lenkerbreite (mm)	360	360	380	400	420
Vorbaulänge (mm)	80	80	90	100	110
Kurbellänge (mm)	165	165	170	170	172.5
Radgrösse	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.