



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	27.5": XS,S,M 29": S,M,L
FARBE	Milky Way
RAHMEN	ALUXX-Grade Aluminum, disc
GABEL	SXC32-2 RL, air spring, QR, alloy steerer XS: 80mm travel (27.5) S: 100mm travel (27.5) / 100mm travel (29) M: 100mm travel (27.5) / 100mm travel (29) L: 100mm travel (29)
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Connect Trail, 31.8mm XS: 670mm (27.5) S: 670mm (27.5) / 670mm (29) M: 750mm (27.5) / 750mm travel (29) L: 750mm (29)
GRIPS	Giant Sole-O
VORBAU	Giant Sport, 7-degree XS: 40mm (27.5) S: 40mm (27.5) / 40mm (29) M: 50mm (27.5) / 50mm travel (29) L: 50mm (29)
SATTELSTÜTZE	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm travel (29) L: 375mm (29)
SATTEL	Liv Sport
PEDALE	MTB caged
ANTRIEB	
SCHALTHEBEL	Shimano Deore M4100, 1x10
UMWERFER	N/A
SCHALTWERK	Shimano Deore M5120
BREMSSEN	Tektro HDC TKD 149, hydraulic, Tektro rotors [F]180mm, [R]160mm
BREMSHEBEL	Tektro TKD 149
KASSETTE	Shimano Deore M4100, 11x42
KETTE	KMC X10
KURBEL	ProWheel Charm, 30t XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (27.5) / 170mm travel (29) L: 175mm (29)
TRETLAGER	cartridge
LAUFRÄDER	
FELGEN	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
NABE	alloy, sealed bearing
SPEICHEN	stainless, 14g
REIFEN	Kenda Booster 27.5 or 29x2.4", wire bead
EXTRAS	2.4" max tire size, 32t max chainring size

MODELL-MERKMALE

- Rahmen: ALUXX-Grade Aluminum, disc
- Gabel: SXC32-2 RL, air spring, QR, alloy steerer XS: 80mm travel (27.5) S: 100mm travel (27.5) / 100mm travel (29) M: 100mm travel (27.5) / 100mm travel (29) L: 100mm travel (29)
- Schalthebel: Shimano Deore M4100, 1x10
- Kurbel: ProWheel Charm, 30t XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (27.5) / 170mm travel (29) L: 175mm (29)
- Farbe: Milky Way

GEOMETRIEDATEN

RAHMEN	XS (27.5")	S (27.5")	S (29")	M (27.5")	M (29")	L (29")
Sitzrohrlänge (mm)	325	365	370	405	420	450
Sitzrohrwinkel	74.0°	74.0°	74.0°	74.0°	74.0°	74.0°
Oberrohrlänge (mm)	542	571	570	594	590	610
Steuerrohr-Länge (mm)	95	100	90	110	95	105
Steuerrohr-Winkel	68.0°	68.0°	68.5°	68.0°	68.5°	68.5°
Gabelneigung (mm)	40	42	51	42	51	51
Trail (mm)	102	98.9	94.3	98.9	94.3	94.3
Radstand (mm)	1072	1104	1119	1128	1139	1160
Kettenstreben-Länge (mm)	440	440	455	440	455	455
Tretlager-Höhe (mm)	40	45	55	45	55	55
Stack (mm)	554	579	596	588	601	610
Reach (mm)	383	405	399	425	418	435
Überstandshöhe (mm)	663	686	705	708	737	757
Lenkerbreite (mm)	730	750	750	750	750	750
Vorbaulänge (mm)	40	40	40	50	50	50
Kurbellänge (mm)	165	165	170	170	170	175
Radgrösse	27.5"	27.5"	29"	27.5"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.