

# EMBOLDEN E+ 2 625



## SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Sport 2, 75Nm, powered by Yamaha
SENSOR	RideControl Dash
DISPLAY	RideControl Dash, full color lcd screen
AKKU	EnergyPak Smart 625, EnergyPak Plus 250Wh range extender compatible
RAHMEN	
GRÖSSEN	XS, S, M, L, (XS: 27.5" / S, M, L: 29")
FARBE	Cosmos Navy
RAHMEN	ALUXX SL-grade aluminum, 125mm travel FlexPoint suspension system, 148x12 rear axle, Universal Derrailleur hanger, 184x44 shock, 1.5~1.8" headset
GABEL	SR Suntour XCR 34 LO-R, 140mm travel, tapered steerer, Lockout, 110x15 thru-axle
DÄMPFER	SR Suntour Raidon R, 190x45mm, custom tuned
KOMponenten	
LENKER	Giant Connect TR Riser 31.8x750mm (XS-S), 780mm (M-L)
GRIFFE	Liv Tactal Pro Single Lock-On Grips
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Liv sylvia E
PEDALE	Aluminum Platform
ANTRIEB	
SCHALTHEBEL	Shimano Deore LinkGlide
UMWERFER	MRP HD2 co-moulded chain guide
SCHALTWERK	Shimano Deore LinkGlide, 10-speed
BREMSEN	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
BREMSHEBEL	Tektro HD-M745 Orion
KASSETTE	Shimano CS-LG400-10, 11-43T, 10-speed LinkGlide
KETTE	Shimano, LinkGlide, CN-LG500
KURBEL	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
TRETLAGER	n/a

LAUFRÄDER	
FELGEN	Giant AM 27.5" (XS), 29"(S, M, L), Tubeless ready, 30mm inner width
NABE	Giant eTracker Boost, [F] 110x15 [R] 148x12mm
SPEICHEN	Stainless Steel
REIFEN	Maxxis Minion DHF 27x2.5"(XS), 29X2.50"(S, M, L) Foldable, TLR, EXO, 60TPI [F]Maxxis Dissector 27.5x2.4"(XS), 29X2.40"(S, M, L) Foldable WT, TLR, EXO, 60TPI [R]
EXTRAS	-
ACCESSORIES	
BELEUCHTUNG	-
SCHLOSS	Torx 25 Battery Lock with built-in Torque limiter
GEPÄCKTRÄGER	-

## GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	380	395	425	455
Sitzrohrwinkel	77.0°	76.5°	76.0°	76.0°
Oberrohrlänge (mm)	565	575	595	615
Steuerrohr-Länge (mm)	105	105	115	125
Steuerrohr-Winkel	66.0°	66.0°	66.0°	66.0°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	121	121	121	121
Radstand (mm)	1201	1199	1215	1237
Kettenstreben-Länge (mm)	468	468	468	468
Tretlager-Höhe (mm)	20	40	40	40
Stack (mm)	601	621	630	639
Reach (mm)	426	426	438	455
Überstandshöhe (mm)	690	710	735	760
Lenkerbreite (mm)	750	750	780	780
Vorbaulänge (mm)	40	40	50	60
Kurbellänge (mm)	165	165	165	165
Radgrösse	27.5"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.