

INTRIGUE X ADVANCED E+ ELITE 2



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY

MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, RideControl GO integrated in T/T
DISPLAY	ANT+ Wireless display compatible
AKKU	EnergyPak Smart 400EnergyPak Plus range extender compatible

RAHMEN

GRÖSSEN	XS, S, M, L
FARBE	Soap Suds/Aged Denim
RAHMEN	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
GABEL	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip Damper, Boost 110x15QR, e-optimized

DÄMPFER	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned
---------	--

KOMPONENTEN

LENKER	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
GRIFFE	Liv Tactal Pro-E Single Lock-On Grips
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Giant Contact Switch, dropper, 30,9mm (XS-S: 100/ M:125/ L:150)
SATTEL	Liv Sylvia E+
PEDALE	n/a

ANTRIEB

SCHALTHEBEL	Shimano SLX
UMWERFER	MRP HD2 co-moulded chain guide
SCHALTWERK	Shimano Deore SLX, 12-speed, Shadow+
BREMSEN	Shimano SLX BR-M7120, 4-piston, hydraulic disc, 203mm
BREMSHEBEL	Shimano Deore SLX, I-spec EV
KASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
KETTE	KMC e.12 Turbo, EcoProteq, e-bike optimized
KURBEL	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (XS:160, S/M: 165, L:170)
TRETLAGER	n/a

LAUFRÄDER

FELGEN	Giant AM 29" [F]/ 27.5" [R], Tubeless ready, 30mm inner width, e-bike optimized
NABE	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPEICHEN	Sapim E-Lite [R] Race [F], e-bike optimized
REIFEN	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohrlänge (mm)	380	400	425	450
Sitzrohrwinkel	77.2° 78.0°	77.2° 78.0°	76.0° 76.7°	76.0° 76.7°
Oberrohrlänge (mm)	557 555	572 570	597 595	622 620
Steuerrohr-Länge (mm)	95	95	100	115
Steuerrohr-Winkel	65.7° 66.5°	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	113 108	113 108	113 108	113 108
Radstand (mm)	1174 1175	1188 1190	1200 1201	1228 1229
Kettenstreben-Länge (mm)	447 447	447 447	447 447	447 447
Tretlager-Höhe (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	606 601	611 605	625 619
Reach (mm)	419 427	434 442	444 452	466 473
Überstandshöhe (mm)	722 730	726 735	717 726	711 723
Lenkerbreite (mm)	760	760	800	800
Vorbaulänge (mm)	40	40	40	50
Kurbellänge (mm)	160	160	165	165
Radgrösse	R27.5" / F29"	R27.5" / F29"	R27.5" / F29"	R27.5" / F29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.