

INTRIGUE X ADVANCED E+ ELITE 3



Spezifikationen

Hybrid Cycling Technology	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, RideControl GO integrated in T/T
DISPLAY	ANT+ Wireless display compatible
AKKU	EnergyPak Smart 400EnergyPak Plus range extender compatible
Rahmen	
GRÖSSEN	XS, S, M, L
FARBE	Mirage/Cordovan
RAHMEN	Advanced-grade composite frame, Aluxx SL-grade rear triangle, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender CompatibleMX (front 29", rear 27.5")
GABEL	RockShox 35 Gold RL DebonAir, 150mm travel, 44mm offset, MotionControl™ rebound and lockout control, 15x110 Boost, Maxle Stealth, e-MTB optimized
DÄMPFER	Rock Shox Deluxe Select R, DebonAir, 185x52.5mm Trunnion mount, custom tuned
Komponenten	
LENKER	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
GRIFFE	Liv Tactal Pro-E Single Lock-On Grips
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Giant Contact Switch, dropper, 30,9mm (XS-S: 100/ M:125/ L:150)
SATTEL	Liv Sylvia E+
PEDALE	n/a
Antrieb	
SCHALTHEBEL	Shimano Deore
UMWERFER	MRP HD2 co-moulded chain guide
SCHALTWERK	Shimano Deore, 12-speed
BREMSEN	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
BREMSHEBEL	Shimano Deore, I-spec EV
KASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
KETTE	KMC e.12 Turbo, EcoProteq, e-bike optimized
KURBEL	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (XS:160, S/M: 165, L:170)
TRETLAGER	n/a

Laufräder	
FELGEN	AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
NABE	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPEICHEN	Sapim E-Lite [R] Race [F], e-bike optimized
REIFEN	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)

Geometriedaten

Rahmen	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohrlänge (mm)	380	400	425	450
Sitzrohrwinkel	77.2° 78.0°	77.2° 78.0°	76.0° 76.7°	76.0° 76.7°
Oberrohrlänge (mm)	557 555	572 570	597 595	622 620
Steuerrohr-Länge (mm)	95	95	100	115
Steuerrohr-Winkel	65.7° 66.5°	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	113 108	113 108	113 108	113 108
Radstand (mm)	1174 1175	1188 1190	1200 1201	1228 1229
Kettenstreben-Länge (mm)	447 447	447 447	447 447	447 447
Tretlager-Höhe (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	606 601	611 605	625 619
Reach (mm)	419 427	434 442	444 452	466 473
Überstandshöhe (mm)	722 730	726 735	717 726	711 723
Lenkerbreite (mm)	760	760	800	800
Vorbaulänge (mm)	40	40	40	50
Kurbellänge (mm)	160	160	165	165
Radgrösse	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

Spezifikations-, Preis- und Farbänderungen vorbehalten.