



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XXS, XS, S, M, L
FARBE	Mulberry Glitter, Kelp Forest/Carbon
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, disc
GABEL	Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings 12x100mm, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Liv Contact SL D-Fuse, 31.8mm, 8-degree flare drop XXS: 410/380mm, XS: 410/380mm, S: 430/400mm, M: 430/400mm, L: 450/420mm
GRIFFE	Liv All Condition
VORBAU	Giant Contact AeroLight XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SATTELSTÜTZE	Giant Contact D-Fuse, composite, 14mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SATTEL	Liv Approach
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano 105
UMWERFER	Shimano 105
SCHALTWERK	Shimano 105
BREMSEN	Shimano 105 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano 105
KASSETTE	Shimano 105, 12-speed, 11x36
KETTE	KMC 12
KURBEL	Shimano FC-R5520, 34/50 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant P-R2 Disc wheelset, alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRAS	tubeless prepared, two bottle cages, 38mm max tire size, fender mount

GEOMETRIEDATEN

RAHMEN	XXS	XS	S	M	L
Sitzrohrlänge (mm)	385	405	435	465	495
Sitzrohrwinkel	75.0°	74.5°	74.5°	74.0°	74.0°
Oberrohrlänge (mm)	500	520	525	535	555
Steuerrohr-Länge (mm)	110	125	145	165	185
Steuerrohr-Winkel	69.8°	71.0°	71.0°	71.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50
Trail (mm)	76	68	68	68	61
Radstand (mm)	989	995	1002	1007	1013
Kettenstreben-Länge (mm)	420	420	420	420	420
Tretlager-Höhe (mm)	75	75	73	73	73
Stack (mm)	510	528	547	566	589
Reach (mm)	363	373	373	373	381
Überstandshöhe (mm)	683	712	737	762	789
Lenkerbreite (mm)	380	380	400	400	420
Vorbaulänge (mm)	70	70	80	90	90
Kurbellänge (mm)	165	165	170	170	172.5
Radgrösse	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.