



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Tiger Red
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
GABEL	Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
DÄMPFER	N/A
KOMponenten	
LENKER	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIFFE	Liv All Condition
VORBAU	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATTELSTÜTZE	Giant Contact SL D-Fuse, composite, -5/+15mm offset
SATTEL	Liv Approach
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-820, 2x11
UMWERFER	Shimano GRX RX-820
SCHALTWERK	Shimano GRX RX-820
BREMSEN	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano GRX RX-820 hydraulic
KASSETTE	Shimano CS-HG710, 12-speed, 11x36
KETTE	KMC X12L-1
KURBEL	Shimano GRX FC-RX820, 31/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant CXR 2 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
NABE	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, 3-pawl driver, CenterLock, 12mm thru-axle
SPEICHEN	Sapim Sprint
REIFEN	CADEX AR, 700x40c, tubeless
EXTRAS	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohrlänge (mm)	390	420	465	500
Sitzrohrwinkel	75.0° 74.0°	75.0° 74.0°	75.0° 74.0°	75.0° 74.0°
Oberrohrlänge (mm)	525 525	535 535	545 545	555 555
Steuerrohr-Länge (mm)	90	110	140	160
Steuerrohr-Winkel	70.0° 70.0°	71.0° 70.0°	71.0° 71.0°	71.0° 71.0°
Gabelneigung (mm)	50	50	50	50
Trail (mm)	78 82	75 79	72 75	72 75
Radstand (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Kettenstreben-Länge (mm)	425 435	425 435	425 435	430 440
Tretlager-Höhe (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Überstandshöhe (mm)	681 688	708 715	748 755	779 786
Lenkerbreite (mm)	400	400	420	420
Vorbaulänge (mm)	50	60	70	80
Kurbellänge (mm)	165	170	172.5	172.5
Radgrösse	700X42C	700X42C	700X42C	700X42C

Spezifikations-, Preis- und Farbänderungen vorbehalten.