



SPEZIFIKATIONEN

| RAHMEN | |
|--------------|---------------------------------------------------------------------------------------------------------------------------------|
| GRÖSSEN | XS, S, M, L |
| FARBE | Kelp Forest |
| RAHMEN | Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage |
| GABEL | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings |
| DÄMPFER | N/A |
| KOMPONENTEN | |
| LENKER | Giant Contact XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm |
| GRIFFE | Liv All Condition |
| VORBAU | Giant Contact AeroLight, -10-degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm |
| SATTELSTÜTZE | Giant D-Fuse, composite, 14mm offset |
| SATTEL | Liv Approach |
| PEDALE | platform pedal [GCS, GTS] no pedal [All other GSC] |
| ANTRIEB | |
| SCHALTHABEL | Shimano GRX RX-610, 2x12 |
| UMWERFER | Shimano GRX RX-820 |
| SCHALTWERK | Shimano GRX RX-820 |
| BREMSEN | Shimano GRX BR-RX400 HRD, Giant MPH rotors [F]160mm, [R]160mm |
| BREMSHEBEL | Shimano GRX RX-610 hydraulic |
| KASSETTE | Shimano CS-HG710, 12-speed, 11x36 |
| KETTE | KMC X12L-1 |
| KURBEL | FSA Omega Modular AGX+, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm |
| TRETLAGER | FSA BB-AL86, press fit |

| LAUFRÄDER | |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| FELGEN | Giant P-X2 Disc, alloy |
| NABE | Giant alloy, 12mm thru-axle |
| SPEICHEN | Sapim |
| REIFEN | Giant Crosscut Grip, 700x40c, tubeless |
| EXTRAS | 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag |

GEOMETRIEDATEN

| RAHMEN | XS | | S | | M | | L | |
|--------------------------|---------------|---------------|---------------|---------------|-------|------|-------|------|
| | SHORT | LONG | SHORT | LONG | SHORT | LONG | SHORT | LONG |
| Sitzrohrlänge (mm) | 390 | 420 | 465 | 500 | | | | |
| Sitzrohrwinkel | 74.5° 74.4° | 74.5° 74.4° | 74.5° 74.4° | 74.5° 74.4° | | | | |
| Oberrohrlänge (mm) | 525 525 | 535 535 | 545 545 | 555 555 | | | | |
| Steuerrohr-Länge (mm) | 90 | 110 | 140 | 160 | | | | |
| Steuerrohr-Winkel | 70.0° 69.9° | 70.5° 70.4° | 71.0° 70.9° | 71.0° 70.9° | | | | |
| Gabelneigung (mm) | 50 | 50 | 50 | 50 | | | | |
| Trail (mm) | 78.4 82 | 75 78.5 | 71.6 75.1 | 71.6 75 | | | | |
| Radstand (mm) | 1012 1022 | 1019 1029 | 1026 1036 | 1043 1052 | | | | |
| Kettenstreben-Länge (mm) | 425 435 | 425 435 | 425 435 | 430 440 | | | | |
| Tretlager-Höhe (mm) | 80 81 | 80 81 | 80 81 | 80 81 | | | | |
| Stack (mm) | 523 524 | 544 545 | 574 575 | 593 594 | | | | |
| Reach (mm) | 380 379 | 384 383 | 386 385 | 391 389 | | | | |
| Überstandshöhe (mm) | 681 688 | 708 715 | 748 755 | 779 786 | | | | |
| Lenkerbreite (mm) | 400 | 400 | 420 | 420 | | | | |
| Vorbaulänge (mm) | 50 | 60 | 70 | 80 | | | | |
| Kurbellänge (mm) | 165 | 170 | 172.5 | 172.5 | | | | |
| Radgrösse | 700 | 700 | 700 | 700 | | | | |

Spezifikations-, Preis- und Farbänderungen vorbehalten.