



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Desert Dawn
RAHMEN	ALUXX SL-grade aluminum front and rear triangles, 140mm Maestro Suspension, flip chip – Maestro 3, flip chip – headset, integrated down tube storage
GABEL	Fox 36 Float Rhythm, 150mm, Grip damper, Boost 15x110 Kabolt X, tapered, 44mm offset
DÄMPFER	Fox Float Performance, 185x52.5, custom tuned for Liv
KOMPONENTEN	
LENKER	Giant Contact TR35, 20mm rise, alloy XS: 760mm, S: 760mm, M: 760mm, L: 780mm
GRIFFE	Liv Tactal Pro Single Lock-on XS/S: 120mm M/L: 130mm
VORBAU	Giant Contact SL, 35mm XS: 40mm, S: 50mm, M: 50mm, L: 50mm
SATTELSTÜTZE	Giant Contact Switch, adjustable dropper, remote XS: 140-170mm travel / 30.9 x 470mm S: 140-170mm travel / 30.9 x 470mm M: 170-200mm travel / 30.9 x 530mm L: 170-200mm travel / 30.9 x 530mm
SATTEL	Liv Sylvia
PEDALE	platform
ANTRIEB	
SCHALTHEBEL	Shimano Deore, 1x12
UMWERFER	N/A
SCHALTWERK	Shimano Deore, Shadow +
BREMSEN	Shimano BR-MT420, hydraulic, Shimano RT-66 [F] 203mm, [R] 180mm
BREMSEBEL	Shimano BL-MT401
KASSETTE	Shimano Deore M6100, 10x51
KETTE	KMC X12
KURBEL	Praxis Cadet M24 Boost, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 170mm
TRETLAGER	Praxis, press fit

LAUFRÄDER	
FELGEN	Giant AM, tubeless ready, sleeve-joint, 30mm inner width XS/S: [F] 29, [R] 27.5 M/L: [F] 29, [R] 29
NABE	alloy, sealed bearing
SPEICHEN	Sapim
REIFEN	Size XS, S, M and L, [F]: Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless Size XS and S, [R]: Maxxis Dissector 27.5x2.4WT, 3C Max Terra, EXO, TR, tubeless Size M and L, [R]: Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	3M tailgate protector, tubeless prepared, integrated down tube storage bag, max tire size 2.5", max chainring size 34t

GEOMETRIEDATEN

RAHMEN	XS			S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sitzrohrlänge (mm)	370			390			420			450		
Seat Post Insertion Depth (mm)	240			260			290			320		
Sitzrohrwinkel	76.2°	76.6°	76.9°	76.2°	76.6°	76.9°	76.8°	77.2°	77.5°	76.8°	77.2°	
Oberrohrlänge (mm)	548	547	546	564	563	562	582	581	580	603	602	601
Steuerrohr-Länge (mm)	95			100			105			110		
Steuerrohr-Winkel	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	
Gabelneigung (mm)	44			44			44			44		
Trail (mm)	134.2	131.3	128.3	134.1	131.3	128.3	134.1	131.3	128.3	134	131.3	
Radstand (mm)	1159	1159	1158	1176	1176	1175	1202	1201	1201	1224	1224	
Kettenstreben-Länge (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Tretlager-Höhe (mm)	25	20	15	25	20	15	40	35	30	40	35	30
Stack (mm)	615	613	610	620	617	614	621	619	616	626	623	620
Reach (mm)	397	401	405	412	415	420	436	440	444	456	459	463
Überstandshöhe (mm)	730	734	738	733	737	742	745	749	754	767	771	775
Lenkerbreite (mm)	760			760			760			780		
Vorbaulänge (mm)	40			50			50			50		
Kurbellänge (mm)	165			170			170			170		
Radgrösse	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Spezifikations-, Preis- und Farbänderungen vorbehalten.